

# BRUTALE 800RR

MV Agusta is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.



PEARL SHOCK RED/PEARL ICE WHITE



METALLIC AVIO GREY/CARBON METALLIC BLACK

## ENGINE

Type	Three cylinder, 4 stroke, 12 valve
Timing system	"D.O.H.C"
Total displacement	798 cm <sup>3</sup> (48.68 cu. in.)
Compression ratio	13.3:1
Starting	Electric
Bore x stroke	79 mm x 54.3 mm (3.1 in. x 2.1 in.)
Max. power - r.p.m. (at the crankshaft)**	103 kW (140 hp) at 13100 r.p.m.
Max. torque - r.p.m.	86 Nm (8.77 kgm) at 10100 r.p.m.
Cooling system	Cooling with separated liquid and oil radiators
Engine management system	Integrated ignition - injection system MVICS 2.0 (Motor & Vehicle Integrated Control System) with six injectors Engine control unit Eldor EM2.0, throttle body full drive by wire Mikuni, pencil-coil with ion-sensing technology, control of detonation and misfire Torque control with four maps, Traction Control with eight levels of intervention
Electronic quick-shift	MV EAS 2.0 (Electronically Assisted Shift up & down)
Clutch	Wet, multi plate with slipper clutch
Transmission	Cassette style; six speed, constant mesh
Primary drive	19/36
Gear ratio	
First gear:	13/37
Second gear:	16/34
Third gear:	18/32
Fourth gear:	19/30
Fifth gear:	21/30
Sixth gear:	22/29
Final drive ratio	16/41

## ELECTRICAL EQUIPMENT

Voltage	12 V
Alternator	350 W at 5000 r.p.m.
Battery	12 V - 8.6 Ah

## DIMENSIONS AND WEIGHT

Wheelbase	1380 mm (54.33 in.)
Overall length	2085 mm (82.09 in.)
Overall width	725 mm (28.54 in.)
Saddle height	810 mm (31.89 in.)
Min. ground clearance	160 mm (6.30 in.)
Trail	95 mm (3.74 in.)
Dry weight	168 kg (370.4 lbs.)
Fuel tank capacity	16.6 l (4.39 U.S. gal.)

## PERFORMANCE

Maximum speed*	245.0 km/h (153.1 mph)
----------------	------------------------

## FRAME

Type	ALS Steel tubular trellis
Rear swing arm pivot plates material	Aluminium alloy

## FRONT SUSPENSION

Type	Marzocchi "UPSIDE DOWN" telescopic hydraulic fork in DLC treated aluminium, with gold colour anodized fork legs and having rebound-compression damping and spring preload external and separate adjustment
Fork dia.	43 mm (1.69 in.)
Fork travel	125 mm (4.92 in.)

## REAR SUSPENSION

Type	Progressive Sachs, single shock absorber with rebound and compression damping and spring preload adjustment
Single sided swing arm material	Aluminium alloy
Wheel travel	125 mm (4.92 in.)

## BRAKES

Front brake	Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking disc and flange
Front brake caliper	Brembo radial-type, with 4 pistons Ø 32 mm (Ø 1.26 in.)
Rear brake	Single steel disc with Ø 220 mm (Ø 8.66 in.) dia.
Rear brake caliper	Brembo with 2 pistons - Ø 34 mm (Ø 1.34 in.)
ABS System	Bosch 9 Plus with RLM (Rear wheel Lift-up Mitigation)

## WHEELS

Front: Material/size	Aluminium alloy 3.50 " x 17 "
Rear: Material/size	Aluminium alloy 5.50 " x 17 "

## TYRES

Front	120/70 - ZR 17 M/C (58 W)
Rear	180/55 - ZR 17 M/C (73 W)

## FAIRING

Material	Thermoplastic
----------	---------------

## CONTENTS

Steering damper	Manually adjustable with 8 settings
-----------------	-------------------------------------

\* Top speed attained on closed course.

\*\* Limited power versions available on demand.

Every country could have a price variation due to local import duties and taxes.