

Zip 50 2T



ZIPPY SINGLE CYLINDER 49CC, 2 STROKE ENGINE WITH ELECTRIC AND KICK-START FUNCTION

*RIDE ON CAR LICENCE QLD SA NT AND WA. SUBJECT TO STATE LAWS**

EASY TO USE AUTOMATIC "TWIST AND GO" CVT TRANSMISSION

LOW EMISSION ENVIRONMENTALLY FRIENDLY EURO 3 COMPLIANT

CLEAR AND EASY TO READ ANALOGUE SPEEDOMETER WITH ODOMETER

LOCKABLE UNDER SEAT STORAGE AND GLOVE BOX PLUS HANDY SHOPPING BAG HOOK

ALLOY WHEELS

BODY MOUNTED SECURITY LOOP

POWERFUL FRONT DISC AND REAR DRUM BRAKES FOR PREDICTABLE STOPPING IN ALL CONDITIONS

WIDE COMFORTABLE SEAT WITH 3 ADJUSTABLE HEIGHTS AND PILLION GRAB STRAP

HARD WEARING MATT EFFECT FLOOR BOARD, GLOVE COMPARTMENT AND TRIMS

2 YEAR UNLIMITED KLM WARRANTY

** Check licence requirements in your state to be sure.*

Technical Specifications	Zip 50 2T
Engine Type	Single cylinder 2-stroke
Cylinder Capacity	49.9 cc
Bore X stroke	39 x 41.8 mm
Max power at shaft	2.5 Kw (3.4hp) at 6500 rpm
Max torque	n/a
Starting	Electric and kick start
Transmission	"Twist and Go" Automatic Transmission (CVT) with Automatic Clutch
Chassis	Steel tube with reinforced plates
Front suspensions	Ø 30 mm telescopic fork - 75mm travel
Rear suspensions	Single arm with dual effect hydraulic shock absorber and coil spring - 74mm travel
Front brake	Ø 175 mm disc
Rear brake	Ø 110 mm drum
Front tyre	Die-cast aluminium alloy, 10"x2.15" Tubeless 100/80-10"
Rear tyre	Die-cast aluminium alloy, 10"x3.00" / Tubeless 120/70-10"
Length	1690 mm
Width	680mm
Wheelbase	1215 mm
Seat height	Adjustable to three positions 750-765-780mm
Dry weight	89 kg
Fuel tank capacity	7.5 litres (1.3 litre reserve included)
Max speed (km/hr)	As per legislation*
Type approval	Euro 2
Consumption (ECE applicable text cycle)	44 km/litre (ECE 47 test cycle)
Consumption @km/h - km/l	40-45 km/l @ 30 km/h